

Art.-Nr.: S10854-00001
Output OC

SOMMER Antriebs- und
Funktechnik GmbH

Hans-Böckler-Straße 27
73230 Kirchheim/Teck
Germany

+49 (0) 900 1800-150

• 0.14 €/min from fixed-line
telephones in Germany.
Mobile charges may vary.



CAUTION!

Smart Home applications may only be operated if a photocell is connected or you have a direct view of the door!



INFORMATION

Only **specialist retailers** can/are permitted to adjust the features and parameters of operators and radio receivers via **SOMlink!**



<https://som4.me/man>

SOMlink settings

Programmable via SOMlink
SOMlink settings required!

DIP setting on STArter S2 board
⇒ DIP switch 2 = OFF

SOMlink menu guidance
⇒ Operators → Sliding gate → Connect operator → STArter S2 → Settings
→ Multi-function relay → Function as operator status display (select)
✓ Save

⇒ → STArter S2 → Settings → Response to command → Button INPUT 1 Selectively Open (select) → Button INPUT 2 Selectively Close (select)
✓ Save

Output OC Art. Nr.: S10854-00001

Output OC:
DC 24 V max. 750 mA

Home Automation

Art.-Nr. S13570-00001_372022_0-DRE_Rev-B_EN

info@sommer.eu
www.sommer.eu

© Copyright 2022

All rights reserved.

STArter S2/S2⁺



Art.-Nr.: 7042V000
Relay

SOMMER Antriebs- und
Funktechnik GmbH

Hans-Böckler-Straße 27
73230 Kirchheim/Teck
Germany

+49 (0) 900 1800-150

• 0.14 €/min from fixed-line
telephones in Germany.
Mobile charges may vary.



CAUTION!

Smart Home applications may only be operated if a photocell is connected or you have a direct view of the door!



INFORMATION

Only **specialist retailers** can/are permitted to adjust the features and parameters of operators and radio receivers via **SOMlink!**



<https://som4.me/man>

SOMlink settings

Programmable via SOMlink
SOMlink settings required!

DIP setting on STArter S2 board
⇒ DIP switch 2 = OFF

SOMlink menu guidance
⇒ Operators → Sliding gate → Connect operator → STArter S2 → Settings → Multi-function relay → Function as operator status display (select)
✓ Save
⇒ → STArter S2 → Settings → Response to command → Button INPUT 1 Selectively Open (select) → Button INPUT 2 Selectively Close (select)
✓ Save

Relay Art. Nr.: 7042V000

Relay:
AC 250 V max. 5 A
DC +24 V max. 5 A

Home Automation

⌚ ≈1 Sec.

Input NC
COM
Input NO