Sliding gate operator

STArter S2⁺

S12735-00001





The smart sliding gate operator STArter $S2^+$ is the ideal operator for gates with a movement range of up to 8 m and a gate weight of 400 kg. His intelligent control offers a wide range of connection options. In addition to convenient operation via radio control system, he can be integrated into the Smart Home systems SOMweb and Delta Dore.





128-bit AES encryption with Rollingcode





Technical data

| Rated voltage | 220-240 V AC |
|------------------------------|--------------|
| Rated frequency | 50/60 Hz |
| Min. temperature | -20 °C |
| Max. temperature | +50 °C |
| IP code | IP54 |
| Max. torque | 11 Nm |
| Max. speed | 240 mm/s |
| Power consumption in standby | 3 W |

| Operating mode | S3 30 % |
|----------------------|---------------|
| Min. movement range | 1.400 mm |
| Max. movement range | 8.000 mm |
| Max. gate weight | 400 kg |
| Gate inclination | - |
| Radio control system | SOMloq2 |
| Radio frequency | FM 868,95 MHz |



A passive rubber profile is sufficient. Active safety contact strips must be used on the main and auxiliary closing edges with the STArter $\rm S2^+$.


Sliding gate operator

STArter S2⁺

S12735-00001



Dimensional drawing



All dimensions are in millimetres. Subject to misprints, errors and technical changes.

Accessories



Memo

Expands the memory of the handheld transmitter to 450 handheld transmitter commands. Allows the use of transmitter management Codemaster⁺.

#10373



Relay

Relay with potential-free changeover contact for activating external lighting or querying the opening status.

#7042V000



Output OC

Open collector output for transmission of a static signal for display of the opening status to Smart Home systems or for activation of additional lighting with 24 V.


#S10854-00001



HomeLink radio receiver module

With the HomeLink radio receiver, the sliding gate operator can be upgraded to the HomeLink radio control system. The sliding gate operator can then be controlled with a HomeLink transmitter integrated in the vehicle.

#S11004-00001



Delta Dore X3D module

The module Integrates the sliding gate operator into the Delta Dore Smart Home system. This allows you to control and query the position of the operator via the Tydom app from Delta Dore.

S11561-00001



Buzzer

Alarm or warning buzzer that outputs an acoustic signal reporting a break-in attempt or during the closing process.

#7043V000