

For sliding gates up to 6 m travel length and 300 kg weight



#3550V000

Safety

- No active safety edges on the main closing edge necessary¹⁾²⁾
- Integrated evaluation for safety edges (without additional charge) provides additional security

Easy to install

- Save time and money during start-up thanks to automatic detection of ideal force values
- Pre-installed test mains cable for start-up with cable pay-off via cable reel
- Maintenance-free operator with long service life

- Defined drive direction control (open/close) or adjustable partial opening for pedestrian function
- 24 V technology with controlled soft run
- With all purpose base plate for easy installation
- Contactless end switch (reed contacts) with fine adjustment

Flexibility

- The operator can be manually unlocked in any position (e.g. in the event of a power failure).
- Plastic bonded steel rack ensures smooth and quiet door operation

TECHNICAL DATA

Temperature range	-20 °C to +50 °C
Nominal voltage	AC 220 - 240 V
Torque	max. 11 Nm
Nominal frequency	50/60 Hz
IP code	IP54

STArter single operator

#3550V000

1x sliding gate operator, control unit, integrated radio receiver (FM 868.8 MHz), universal installation bracket (H = 15 mm)

STArter complete set

#3540V000

1x sliding gate operator, control unit, 4 m steel rack bonded with plastic, integrated radio receiver (FM 868.8 MHz), universal installation bracket (H = 15 mm), 4-command transmitter

1) must observe the standards and guidelines given in the declaration of incorporation, especially DIN EN 13241-1. 2) does not apply for STArter+.

Last updated: 02/2015. Literal errors, errors and technical changes excepted.